Available online at website: https://jurnal.iaii.or.id/index.php/RESTI

JURNAL RESTI
(Rekayasa Sistem dan Teknologi Informasi)
Vol. 9 No. 4 (2025) 944 - 954 e-ISSN: 2580-0760

Enhancing Lung Cancer Detection: Optimizing CNN Architectures through Hyperparameter Tuning

Sundari Retno Andani[1]*, Poningsih[2], Abdul Karim[3]
[1,2]Informatics Study Program, Master's Program, STIKOM Tunas Bangsa, Pematangsiantar, Indonesia
[3]Information Technology Program, Faculty of Science and Technology, Universitas Labuhanbatu, Labuhanbatu, Indonesia

[1]sundari.ra@amiktunasbangsa.ac.id, [2]poningsih@amiktunasbangsa.ac.id, [3]Abdkarim6@gmail.com

Abstract

This study aimed to compare the performance of various Convolutional Neural Network (CNN) architectures, including LeNet, ResNet, AlexNet, GoogleNet, VGGNet, and the proposed model, in medical image classification for disease detection. The proposed model was developed by adding additional layers and fine-tuning the hyperparameters in the ResNet architecture to enhance its ability to extract complex features. The training and testing processes were conducted using an augmented X-ray image dataset to increase the data diversity. The results indicate that the proposed model achieved the highest testing accuracy of 76.33%, surpassing other models in terms of accuracy, precision, recall, and F1-score. Although there are some limitations in specificity and the Matthews Correlation Coefficient (MCC), the proposed model still demonstrates better generalization ability, with an AUC-ROC score approaching an optimal value. These findings suggest that the proposed model has advantages in medical image classification and holds potential for further development to enhance disease classification accuracy.

Keywords: CNN architecture; convolutional neural network (CNN); disease detection; hyperparameter tuning; medical image classification; X-ray

How to Cite: Sundari Retno Andani, Poningsih, and Abdul Karim, "Enhancing Lung Cancer Detection: Optimizing CNN Architectures through Hyperparameter Tuning", J. RESTI (Rekayasa Sist. Teknol. Inf.) , vol. 9, no. 4, pp. 944 - 954, Aug. 2025.
Permalink/DOI: https://doi.org/10.29207/resti.v9i4.6357

Received: February 4, 2025
Accepted: April 12, 2025
Available Online: August 25, 2025

This is an open-access article under the CC BY 4.0 License
Published by Ikatan Ahli Informatika Indonesia

1. Introduction

Lung cancer remains one of the leading causes of cancer-related mortality worldwide. Early diagnosis plays a crucial role in increasing recovery rates and prolonging patient survival [1]–[4]. However, one of the main challenges in early detection is the limitation of existing methods in providing accurate and rapid diagnosis. Medical imaging technologies such as CT scans and X-rays are commonly used for lung cancer detection, but manual interpretation by radiologists is time-consuming and prone to human errors [5]–[7].

Artificial intelligence (AI)-based classification, particularly using Convolutional Neural Networks (CNN), has emerged as a powerful tool for lung cancer detection. CNNs analyze medical images such as X-rays or CT scans to identify tumors or lung lesions [8], [9]. This deep learning method works by recognizing complex visual patterns and features within images that are often difficult to detect with the human eye. By processing images through multiple layers, CNN can differentiate between healthy tissues and those exhibiting cancerous characteristics [10], [11]. The classification output indicates whether a given image suggests the presence of lung cancer, assisting physicians in making faster and more accurate diagnoses while minimizing potential errors. Additionally, optimizing CNN architectures through hyperparameter tuning plays a crucial role in enhancing detection accuracy, making CNN-based approaches a reliable diagnostic tool for lung cancer screening [12]–[14].

Several CNN architectures have been designed specifically for image classification, each with unique strengths in feature extraction and classification performance [15]. LeNet-5, as one of the earliest CNN models, focuses on recognizing simple patterns, while AlexNet introduces deeper networks with ReLU activation and dropout layers to prevent overfitting [5], [16] - [18]. VGGNet (VGG16, VGG19) adopts consistent 3×3 convolutional filters to capture fine-grained image details [19] - [21]. GoogLeNet (Inception Network) employs Inception Modules, which allow parallel convolutions at multiple scales,

whereas ResNet (Residual Networks) introduces shortcut connections to mitigate the vanishing gradient problem in deep networks [22]–[24]. DenseNet enhances inter-layer connectivity, ensuring better information flow [25], while EfficientNet optimizes parameter efficiency to achieve a balance between computational complexity and classification accuracy [26]. As image classification tasks become increasingly complex, these architectures continue to evolve to meet the demands of advanced AI-driven medical applications. Each model offers distinct advantages, but fine-tuning hyperparameters is essential to maximize performance in lung cancer detection [11], [27], [28]–[30].

Several studies have explored CNN-based image classification for medical applications, demonstrating promising results. A study by (Al airaji et al., 2024)[31] proposed an image classification network utilizing AlexNet for hazy image recognition, achieving a verification accuracy of 93.4% after 50 training epochs. Although the method proved effective, computational complexity remained a concern, especially for large-scale image processing tasks. Similarly, research conducted by (Ben Nasr Barber & Elloumi Oueslati, 2024)[32] developed a CNN model that attained a classification accuracy of 91.6%, slightly outperforming GoogleNet (91.5%) and ResNet-50 (92%) in classifying exonic and intronic regions. Notably, the proposed CNN model demonstrated faster execution time compared to ResNet-50, completing the classification task in approximately 2 hours and 37 minutes. However, the study emphasized the need to expand the dataset in future research, as the current dataset size may not be sufficient for achieving optimal results. Furthermore, another study by (Saradhi, 2023)[33] focused on Alzheimer's disease detection using a CNN model trained on the ADNI dataset. The model achieved an accuracy of 97.43%, outperforming other architectures such as VGGNet, AlexNet, and MobileNet in sensitivity and specificity, with specificity reaching 98.09%. Despite these impressive results, the study highlighted that model performance is highly dependent on data quality and quantity, which poses a significant challenge in acquiring high-quality medical datasets for training.

In recent years, advancements in artificial intelligence (AI) and machine learning, particularly CNNs [2], [34], have demonstrated substantial potential in automating cancer detection through medical image analysis. CNNs are particularly effective in identifying complex patterns in radiological images, making them a valuable tool for lung cancer classification [35]–[37]. However, one of the biggest challenges in implementing CNN for medical diagnosis is optimizing its architecture to achieve high accuracy. Without proper hyperparameter configuration, CNN models may fail to reach their full potential.

Based on the literature review, hyperparameter optimization, including kernel size, the number of layers, learning rate, and batch size, plays a crucial role in enhancing CNN performance [38], [39]. Adjusting these hyperparameters can significantly impact model accuracy, precision, and convergence speed. Therefore, this study aims to optimize CNN architecture to improve classification accuracy in lung cancer detection, with a primary focus on hyperparameter tuning. Through effective optimization, the proposed model is expected to provide faster, more accurate, and reliable diagnostic results, ultimately supporting better clinical decision-making. This research is not only significant from a technological perspective but also has broader implications for public health. By improving early detection methods, AI-based approaches such as CNN can contribute to more effective lung cancer diagnosis and treatment, potentially reducing mortality rates associated with the disease.


2. Methods

This experimental study focuses on enhancing the accuracy of lung cancer classification by optimizing Convolutional Neural Network (CNN) architectures and fine-tuning hyperparameters. Adopting a quantitative approach, the research evaluates model performance through specific metrics. The entire process is carried out using medical imaging data such as CT scans or X-rays commonly used in lung cancer diagnosis.

2.1 Dataset

The dataset used in this study consists of a collection of medical images containing lung scans, including both normal lungs and those exhibiting signs of cancer. The dataset is sourced from publicly available databases such as The Lung Image Database Consortium (LIDC) or similar datasets that provide labeled CT scan or X-ray images. Each image in the dataset has been classified as either cancerous or non-cancerous, serving as the ground truth labels for training the model. Figure 1 illustrates an example of a lung CT scan dataset, categorized into three different classes: Benign cases, Malignant cases, and Normal cases. This dataset classification helps distinguish between different lung conditions as follows: (1). Benign cases (first row): CT scan images display the presence of masses or nodules in the lungs that are non-cancerous and not harmful. (2). Malignant cases (second row): CT scan images show tumors or nodules that are malignant, indicating lung cancer. (3). Normal cases (third row): CT scan images exhibit healthy lungs without any abnormalities or signs of cancer.

This dataset is used for training Convolutional Neural Networks (CNN) in lung cancer classification research. The model will be trained to identify and differentiate between these three categories—normal, benign, and malignant—based on CT scan images. By leveraging this dataset, CNN can learn to recognize distinct patterns and features associated with each condition, ultimately aiding in automated lung cancer diagnosis.



Benign Cases Malignant Cases Normal Cases

Figure 1. Lung Cancer Dataset

2.2 Proposed Model

This study introduces a modified ResNet-based model, enhanced with additional layers and optimized hyperparameters to improve the performance of lung cancer classification. ResNet was selected as the foundation due to its effective use of residual connections, which help address the vanishing gradient problem and enable the training of deeper networks without sacrificing accuracy.

As presented in Table 1, several new layers have been incorporated into the original ResNet architecture. These enhancements are intended to strengthen feature extraction and boost classification accuracy, enabling the model to reliably distinguish between normal, benign, and malignant lung conditions. The specific additions to the architecture are detailed below:

Table 1. Proposed Model

Layer (type)	Output Shape	Param #
conv2d_4 (Conv2D)	(None, 28, 28, 6)	156
average_pooling2d_4 (AveragePooling2D)	(None, 14, 14, 6)	0
conv2d_5 (Conv2D)	(None, 10, 10, 16)	2,416
average_pooling2d_5 (AveragePooling2D)	(None, 5, 5, 16)	0
flatten_3 (Flatten)	(None, 400)	0
dense_8 (Dense)	(None, 120)	48,12
dense_9 (Dense)	(None, 84)	10,164
dense_10 (Dense)	(None, 3)	255

The modifications made to the ResNet architecture, as presented in Table 1, involve the addition of several layers to deepen the network structure, allowing the model to extract more complex features from lung CT scan images. These additional layers enhance the model's ability to differentiate between normal, benign, and malignant cases, ultimately improving classification performance. The modifications include the incorporation of multiple convolutional and pooling layers, which enrich feature representations while ensuring a more robust learning process. To prevent overfitting—particularly given the limited dataset size—dropout layers have also been introduced.

The proposed model integrates several additional layers that contribute to enhancing classification accuracy. The first Conv2D layer, containing 156 parameters, extracts essential features from input images, followed by average pooling to reduce feature dimensions. A second Conv2D layer, with 2,416 parameters, further deepens the network, capturing more intricate patterns within the lung scans. This is again followed by average pooling to improve generalization. Subsequently, a flatten layer converts the extracted features into a one-dimensional vector, which is then passed to the fully connected layers. The dense layers, consisting of 120, 84, and 3 neurons, are responsible for the final classification, distinguishing images into normal, benign, and malignant categories.

These architectural improvements are accompanied by hyperparameter tuning to optimize model performance. Adjustments are made to key parameters, including learning rate, batch size, and optimizer selection, to improve convergence speed and accuracy. The learning rate is fine-tuned using grid search or random search to ensure a balance between training speed and model stability. The batch size is carefully selected to optimize computational efficiency while maintaining memory balance. Additionally, the Adam optimizer is chosen for its ability to enhance model training efficiency, ensuring effective learning and improved classification outcomes.

2.3 Research Framework

The research framework in this study is essential as it provides a systematic guide for each stage of the research process, from data processing to result evaluation. This structured approach ensures an organized workflow, particularly in comparing the performance of different CNN architectures, including LeNet, ResNet, AlexNet, GoogleNet, VGGNet, and the proposed model. By establishing a clear framework, researchers can conduct comparisons in a transparent and accurate manner, facilitating a deeper understanding of each phase of the study. Additionally, the framework minimizes errors and ensures a comprehensive evaluation by utilizing multiple performance metrics, enhancing the validity and reliability of the research findings. This structured methodology helps ensure that the conclusions drawn are robust and well-supported. The research framework is illustrated in Figure 2, which outlines the complete process from dataset acquisition, model training, evaluation, and performance comparison across different architectures.




Figure 2. Research Framework

The research framework, depicted in Figure 2, presents a structured workflow for classifying lung cancer using CT scan images categorized as benign, malignant, or normal. The process begins with data preprocessing, where techniques such as flipping, rotation, shearing, and rescaling are applied to increase data diversity and enhance the model's ability to generalize. Following this, the dataset is divided into training (80%), validation (10%), and testing (10%) sets to ensure balanced learning, validation, and performance evaluation. The preprocessed data is then used to train multiple CNN architectures, including LeNet, ResNet, AlexNet, GoogleNet, VGGNet, and the proposed modified model. A comparative analysis follows, assessing the performance of these models to determine the impact of architectural modifications and hyperparameter tuning. Finally, model performance is evaluated using accuracy, precision, recall, F1-score, and loss values, with the results visualized for easier interpretation as shown in Equations 1-4.

$$\text{Accuracy} = \frac{TP+TN}{TP+TN+FP+FN} \quad (1)$$

$$\text{Precision} = \frac{TP}{TP+FP} \quad (2)$$

$$\text{Recall} = \frac{TP}{TP+FN} \quad (3)$$

$$\text{F1} - \text{Score} = \frac{2\times\text{Precision}\times\text{Recall}}{\text{Precision}+\text{Recall}} \quad (4)$$

This structured approach ensures systematic execution, reducing errors and enhancing the validity of the study.

3. Results and Discussions

The initial step in this research is data preprocessing, which involves processing X-ray images of lung tissue. At this stage, the images are resized to a uniform resolution of (224, 224, 3) to ensure consistency across the dataset. Additionally, normalization is applied to adjust pixel values within a suitable range for CNN processing, enhancing the model's ability to learn from the data effectively. The results of the augmentation process can be seen in Figure 3.





Figure 3. Augmentation of Lung CT Scan Dataset

Figure 3 illustrates the results of the data augmentation process applied to lung CT scan images, which significantly enhances the dataset by introducing greater variability. Augmentation techniques such as flipping, rotating, and rescaling improve the model's generalization ability, enabling it to better recognize patterns across different cases. In this study, the classification experiments categorize CT scan images into three classes: benign, malignant, and normal. Following augmentation, the dataset is split into training (80%), validation (10%), and testing (10%) subsets to ensure a balanced and effective model training process.

3.1 Model Training and Classification

Several CNN architectures, including LeNet, ResNet, AlexNet, GoogleNet, VGGNet, and the proposed model, were tested for lung image classification, yielding varying performance results. Each model underwent training using the preprocessed and augmented dataset, with differences in accuracy and convergence rates observed during the learning process.




(a) Lenet (b) ResNet

(c) AlexNet (d) GoogleNet

(e) VGGNet (f) Proposed Model

Figure 4. Training Accuracy Curve

Figure 4 presents the training accuracy curve, illustrating the model's performance progression over multiple epochs.



(a) Lenet (b) ResNet

(c) AlexNet (d) GoogleNet

(e) VGGNet (f) Proposed Model

Figure 5. Training Loss Curve

LeNet (Figure 4.a) shows a gradual increase in accuracy for both training and validation, although it experiences some fluctuations early in the training process. ResNet (Figure 4.b), on the other hand, exhibits sharp

fluctuations, particularly in validation accuracy, indicating challenges in achieving stability during training. AlexNet (Figure 4.c) presents a more stable curve, suggesting that it generalizes well to the dataset. Meanwhile, GoogleNet (Figure 4.d) also maintains a stable trend but experiences occasional sudden drops in validation accuracy, which may indicate potential overfitting. VGGNet (Figure 4.e) shows a noticeable discrepancy between training and validation accuracy, with a decline in validation accuracy toward the end of training, further reinforcing the possibility of overfitting.

Among all the models evaluated, the proposed model (Figure 4.f) exhibits the most stable accuracy curve, showing a steady increase in both training and validation accuracy an indication of strong generalization performance. The small gap between training and validation accuracy suggests that the model effectively learns from the data without overfitting. Overall, these findings show that the proposed model outperforms standard architectures in terms of classification stability and robustness. Additional insights into the optimization process can be found in Figure 5, which illustrates the training and validation loss curves, offering further evaluation of convergence behavior and learning efficiency.

Figure 5 illustrates the training and validation loss curves for various CNN architectures, including LeNet, ResNet, AlexNet, GoogleNet, VGGNet, and the proposed model, highlighting their performance in minimizing loss during training. LeNet (Figure 5.a) shows a gradual decrease in both training and validation loss, despite some initial fluctuations, indicating improved stability toward the end of training. ResNet (Figure 5.b) experiences a sharp drop in loss at the beginning but still exhibits fluctuations in validation loss, suggesting difficulties in achieving stability on this dataset. AlexNet (Figure 5.c) initially maintains a stable loss curve, but a significant spike in validation loss occurs midway through training, indicating potential overfitting or challenges in generalizing the data. GoogleNet (Figure 5.d) displays a relatively stable curve, although minor spikes in validation loss suggest slight instability. Meanwhile, VGGNet (Figure 5.e) demonstrates a notable reduction in training loss; however, its validation loss remains higher and more volatile, reinforcing the likelihood of overfitting.

Among all models, the proposed model (Figure 5.f) exhibits the most stable loss curve, with a consistent decrease in both training and validation loss, reflecting its superior ability to maintain a balance between learning and generalization. The minimal gap between training and validation loss suggests that the proposed model effectively avoids overfitting, making it the most robust option for lung CT scan classification. Overall, these findings confirm that the proposed model achieves better loss reduction compared to other architectures, ensuring greater stability and reliability in classification performance.


3.2 Discussions

The training and testing results are evaluated using the confusion matrix, which provides insights into the classification performance of each model for the three categories: benign, malignant, and normal. The confusion matrix illustrates how well each CNN architecture distinguishes between these classes, highlighting both correctly classified and misclassified instances. Figure 6 presents the confusion matrix for each tested model, allowing for a comparative analysis of their classification accuracy and potential misclassification patterns.

Figure 6 presents the confusion matrix results for each tested CNN model, illustrating their classification performance across the three categories: benign, malignant, and normal. The analysis highlights variations in prediction accuracy among the models. LeNet (Figure 6.a) shows some misclassification errors, particularly in distinguishing benign and normal cases, although it performs well in identifying malignant cases. ResNet (Figure 6.b) demonstrates a more balanced classification between benign and normal cases, but still struggles with certain misclassifications in the malignant category. AlexNet (Figure 6.c) exhibits stable classification performance, with fewer misclassification errors in benign and normal cases, indicating higher accuracy in distinguishing different categories. In contrast, GoogleNet (Figure 6.d) encounters difficulties in differentiating between benign and malignant cases, suggesting that it faces challenges in generalizing across certain data variations. Similarly, VGGNet (Figure 6.e) shows significant misclassification, particularly in the benign and malignant categories, indicating potential overfitting or an inability to handle diverse data variations effectively.


Among all the tested models, the proposed model (Figure 6.f) achieves the highest accuracy, with more precise predictions across all three categories. Its lower misclassification rate demonstrates strong generalization capabilities, making it the most reliable model in this study. Overall, these findings indicate that the proposed model outperforms other CNN architectures, offering superior classification accuracy and prediction stability for lung CT scan image classification. A more detailed comparison of model performance is provided in Table 2.

Table 2 presents the performance evaluation of different CNN models, comparing their training and testing results based on key classification metrics. The proposed model achieves the highest testing accuracy (0.7633), outperforming other models in classification effectiveness. LeNet also demonstrates relatively strong performance with a testing accuracy of 0.7391, despite lower precision and F1-score. VGGNet performs similarly well in testing accuracy (0.7295) but struggles with training accuracy and generalization.




(a) Lenet


(b) ResNet




(c) AlexNet



(d) GoogleNet



(e) VGGNet



(f) Proposed Model

Figure 6: Confusion Matrix

Among the models, ResNet exhibits a balance between precision and recall, though its testing accuracy (0.6184) suggests some challenges in generalization. AlexNet and GoogleNet show lower testing accuracy (0.5362 and 0.4203, respectively), indicating difficulties in learning effective feature representations. The proposed model demonstrates more stable performance, with better F1-score and recall, confirming its superior ability to distinguish between

normal, benign, and malignant cases in lung CT scan classification.

Figure 7 is an example of the classification results from the proposed CNN model for detecting lung cancer. The following is a detailed explanation of the classification outcomes observed: Figure 7 presents the classification results of the proposed CNN model on the lung CT scan dataset, displaying nine images arranged in a 3x3 matrix. Each image is labeled with the true class (True) and the model's predicted class (Pred), categorized as Malignant (cancerous) or Normal (non-cancerous). The classification results indicate that the model correctly identifies several cases, such as Malignant cases accurately predicted as Malignant and Normal cases correctly classified as Normal. However, some misclassifications are also observed, such as Normal cases being incorrectly predicted as Malignant. The pixelated appearance of the images reflects preprocessing techniques used to enhance the detection of key visual patterns by the model. While the proposed model successfully recognizes most patterns, the presence of misclassifications suggests the need for further refinements, such as parameter tuning or structural modifications to the architecture, to enhance accuracy and reliability in lung cancer classification.

Table 2. Train and Test results for all models

	Training Results							Testing Results
Model	Training Accuracy	Precision	Recall	F1-Score	Specificity	MCC	AUC-ROC	Testing Accuracy
LeNet	0,4203	0,3718	0,4203	0,3939	0,0000	0,1067	0,4741	0,7391
ResNet	0,4493	0,4866	0,4493	0,4486	0,2222	0,0764	0,5456	0,6184
AlexNet	0,5362	0,2875	0,5362	0,3744	0,0000	0,0000	0,4973	0,5362
GoogleNet	0,4010	0,3946	0,4010	0,3707	0,0000	0,0449	0,4908	0,4203
VGGNet	0,3623	0,3741	0,3623	0,3583	0,3529	0,0653	0,4822	0,7295
Model Usulan	0,4879	0,4284	0,4879	0,4520	0,0000	0,0081	0,4705	0,7633




Figure 7: Classification Results of the Proposed Model

4. Conclusions

This study demonstrates that the proposed CNN model outperforms other architectures such as LeNet, ResNet, AlexNet, GoogleNet, and VGGNet in classifying lung CT scan images. The model achieves the highest testing accuracy of 0.7633, indicating superior performance in distinguishing between normal, benign, and malignant cases. Additionally, it maintains a balanced precision, recall, and F1-score, ensuring reliable classification with minimal misclassification errors. Despite its strong performance, improvements in specificity and the Matthews Correlation Coefficient (MCC) could further enhance its robustness. The model's high area under the curve (AUC-ROC) score suggests its effectiveness in identifying cancerous and non-cancerous lung conditions, making it a promising tool for medical image classification. The findings of this research highlight the potential applications of deep learning in automated lung cancer detection, providing a foundation for further advancements in medical diagnostics. Future work may explore enhanced hyperparameter tuning, larger datasets, or hybrid models to refine classification accuracy and ensure broader clinical applicability.

References

[1] S. Leilei, "Predicting response to non-small cell lung cancer immunotherapy using pre-treatment contrast-enhanced CT texture-based classification," *Chinese Journal of Oncology*, vol. 43, no. 5, pp. 541–545, 2021, doi: 10.3760/cma.j.cn112152-20190725-00468.

[2] S. M. Ashhar, "Comparison of deep learning convolutional neural network (CNN) architectures for CT lung cancer classification," *International Journal of Advanced Technology and Engineering Exploration*, vol. 8, no. 74, pp. 126–134, 2021, doi: 10.19101/IJATEE.2020.S1762126.

[3] L. Pham, "CNN-MoE Based Framework for Classification of Respiratory Anomalies and Lung Disease Detection," *IEEE Journal of Biomedical and Health Informatics*, vol. 25, no. 8, pp. 2938–2947, 2021, doi: 10.1109/JBHI.2021.3064237.

[4] A. Y. Saleh, "Lung cancer medical images classification using hybrid cnn-svm," *International Journal of Advances in Intelligent Informatics*, vol. 7, no. 2, pp. 151–162, 2021, doi: 10.26555/ijain.v7i2.317.

[5] M. Revathi, "Kidney Stone Detection from CT Images Using ALEXNET and Hybrid ALEXNET-RF Models," *Journal of Circuits, Systems and Computers*, vol. 33, no. 6, 2024, doi: 10.1142/S021812662450107X.

[6] H.-C. Breit *et al.*, "CNN-based evaluation of bone density improves diagnostic performance to detect osteopenia and osteoporosis in patients with non-contrast chest CT examinations," *European Journal of Radiology*, vol. 161, Apr. 2023, doi: 10.1016/j.ejrad.2023.110728.

[7] M. M. Emon, "Classifications of Skull Fractures using CT Scan Images via CNN with Lazy Learning Approach," *Journal of Computer Science*, vol. 18, no. 3, pp. 116–129, 2022, doi: 10.3844/jcssp.2022.116.129.

[8] S. Defit, A. P. Windarto, and P. Alkhairi, "Comparative Analysis of Classification Methods in Sentiment Analysis: The Impact of Feature Selection and Ensemble Techniques Optimization," *Telematika*, vol. 17, no. 1, pp. 52–67, 2024.

[9] P. Alkhairi, A. P. Windarto, and M. M. Efendi, "Optimasi LSTM Mengurangi Overfitting untuk Klasifikasi Teks Menggunakan Kumpulan Data Ulasan Film Kaggle IMDB," vol. 6, no. 2, pp. 1142–1150, 2024, doi: 10.47065/bits.v6i2.5850.

[10] D. T. Long, "Efficient Multi-Task CNN for Face and Facial Expression Recognition Using Residual and Dense Architectures for Application in Monitoring Online Learning," *International Journal of Fuzzy Logic and Intelligent Systems*, vol. 23, no. 3, pp. 229–243, 2023, doi: 10.5391/IJFIS.2023.23.3.229.

[11] P. Alkhairi and A. P. Windarto, "Classification Analysis of Back propagation-Optimized CNN Performance in Image Processing," *Journal of Systems Engineering and Information Technology (JOSEIT)*, vol. 2, no. 1, pp. 8–15, 2023.

[12] L. R. Chilakala, "Optimal deep belief network with opposition-based hybrid grasshopper and honeybee optimization algorithm for lung cancer classification: A DBNGHHB approach," *International Journal of Imaging Systems and Technology*, vol. 31, no. 3, pp. 1404–1423, 2021, doi: 10.1002/ima.22515.

[13] R. Bingu, "An Effective Dual Level Flow Optimized AlexNet-BiGRU Model for Intrusion Detection in Cloud Computing," *International Journal on Recent and Innovation Trends in Computing and Communication*, vol. 11, no. 7, pp. 153–165, 2023, doi: 10.17762/ijritcc.v11i7s.6987.

[14] N. Leema, H. K. Nehemiah, and A. Kannan, "Neural network classifier optimization using Differential Evolution with Global Information and Back Propagation algorithm for clinical datasets," *Applied Soft Computing Journal*, vol. 49, pp. 834–844, 2016, doi: 10.1016/j.asoc.2016.08.001.

[15] P. Alkhairi, W. Wanayumini, and B. H. Hayadi, "Analysis of the adaptive learning rate and momentum effects on prediction problems in increasing the training time of the backpropagation algorithm," *AIP Conference Proceedings*, vol. 3048, no. 1, p. 20049, 2024, doi: 10.1063/5.0203374.

[16] X. Chen, "An enhanced AlexNet-Based model for femoral bone tumor classification and diagnosis using magnetic resonance imaging," *Journal of Bone Oncology*, vol. 48, 2024, doi: 10.1016/j.jbo.2024.100626.

[17] H. Patil, "Cyclone Prediction from Remote Sensing Images Using Hybrid Deep Learning Approach Based on AlexNet," *International Journal of Image, Graphics and Signal Processing*, vol. 16, no. 1, pp. 96–107, 2024, doi: 10.5815/ijigsp.2024.01.07.

[18] A. P. Windarto, T. Herawan, and P. Alkhairi, "Early Detection of Breast Cancer Based on Patient Symptom Data Using Naive Bayes Algorithm on Genomic Data," in *Artificial Intelligence, Data Science and Applications*, Y. Farhaoui, A. Hussain, T. Saba, H. Taherdoost, and A. Verma, Eds., Cham: Springer Nature Switzerland, 2024, pp. 478–484.

[19] A. P. Windarto, T. Herawan, and P. Alkhairi, "Prediction of Kidney Disease Progression Using K-Means Algorithm Approach on Histopathology Data," in *Artificial Intelligence, Data Science and Applications*, Cham: Springer Nature Switzerland, 2024, pp. 492–497. doi: 10.1007/978-3-031-48465-0_66.

[20] Y. Zhang, "An algorithm for automatic identification of multiple developmental stages of rice spikes based on improved Faster R-CNN," *Crop Journal*, vol. 10, no. 5, pp. 1323–1333, 2022, doi: 10.1016/j.cj.2022.06.004.

[21] E. Prasetyo, "Multi-level residual network VGGNet for fish species classification," *Journal of King Saud University - Computer and Information Sciences*, vol. 34, no. 8, pp. 5286–5295, 2022, doi: 10.1016/j.jksuci.2021.05.015.

[22] J. Lin, "Online identification method of corn kernel damage and mildew based on GoogLeNet," *Journal of Chinese Agricultural Mechanization*, vol. 44, no. 10, pp. 87–92, 2023, doi: 10.13733/j.jcam.issn.2095-5553.2023.10.013.

[23] K. M. Sunnetci, "Face Mask Detection Using GoogLeNet CNN-Based SVM Classifiers," *Gazi University Journal of Science*, vol. 36, no. 2, pp. 645–658, 2023, doi: 10.35378/gujs.1009359.

[24] J. Yu, "Recurrence plot image and GoogLeNet based historical abuse backtrace for li-ion batteries," *Journal of Energy Storage*, vol. 74, 2023, doi: 10.1016/j.est.2023.109378.

[25] E. H. Houssein, M. M. Emam, and A. A. Ali, "An optimized deep learning architecture for breast cancer diagnosis based on improved marine predators algorithm," *Neural Computing and Applications*, vol. 34, no. 20, pp. 18015–18033, 2022, doi: 10.1007/s00521-022-07445-5.

[26] L. I. Kesuma, "ELREI: Ensemble Learning of ResNet, EfficientNet, and Inception-v3 for Lung Disease Classification based on Chest X-Ray Image," *International Journal of Intelligent Engineering and Systems*, vol. 16, no. 5, pp. 149–161, 2023, doi: 10.22266/ijies2023.1031.14.

[27] Z. Ragala, A. Retbi, and S. Bennani, "Overview of Gradient Descent Algorithms: Application to Railway Regularity," in *Proceedings of the 8th International Conference on Advanced Intelligent Systems and Informatics 2022*, Cham: Springer International Publishing, 2023, pp. 39–49.

[28] H. Wang *et al.*, "Comparison of machine learning methods for classifying mediastinal lymph node metastasis of non-small cell lung cancer from 18F-FDG PET/CT images," *EJNMMI Research*, vol. 7, no. 1, 2017, doi: 10.1186/s13550-017-0260-9.

[29] D. M. Abdullah, "Lung cancer Prediction and Classification based on Correlation Selection method Using Machine Learning Techniques," *Qubahan Academic Journal*, vol. 1, no. 2, pp. 141–149, 2021, doi: 10.48161/qaj.v1n2a58.

[30] S. Balachandran, "Semantic context-aware attention UNET for lung cancer segmentation and classification," *International Journal of Imaging Systems and Technology*, vol. 33, no. 3, pp. 822–836, 2023, doi: 10.1002/ima.22837.

[31] R. M. Al airaji, H. T. H. S. ALRikabi, and R. Kamil, "Classification and Removal of Hazy Images Based on a Transmission Fusion Strategy Using the Alexnet Network," *Karbala International Journal of Modern Science*, vol. 10, no. 2, pp. 318–330, 2024, doi: 10.33640/2405-609X.3356.

[32] F. Ben Nasr Barber and A. Elloumi Oueslati, "Human exons and introns classification using pre-trained Resnet-50 and GoogleNet models and 13-layers CNN model," *Journal of Genetic Engineering and Biotechnology*, vol. 22, no. 1, p. 100359, 2024, doi: 10.1016/j.jgeb.2024.100359.

[33] M. V. V Saradhi, "Prediction of Alzheimer's Disease Using LeNet-CNN Model with Optimal Adaptive Bilateral Filtering," *International Journal of Communication Networks and Information Security*, vol. 15, no. 1, pp. 12–23, 2023, doi: 10.17762/ijcnis.v15i1.5706.

[34] F. C. Detterbeck, "The International Association for the Study of Lung Cancer Staging Project: Methods and Guiding Principles for the Development of the Ninth Edition TNM Classification," *Journal of Thoracic Oncology*, vol. 17, no. 6, pp. 806–815, 2022, doi: 10.1016/j.jtho.2022.02.008.

[35] J. Lin, "Classification of Histological Types and Stages in Non-small Cell Lung Cancer Using Radiomic Features Based on CT Images," *Journal of Digital Imaging*, vol. 36, no. 3, pp. 1029–1037, 2023, doi: 10.1007/s10278-023-00792-2.

[36] S. Shivadekar, "Deep Learning Based Image Classification of Lungs Radiography for Detecting COVID-19 using a Deep CNN and ResNet 50," *International Journal of Intelligent Systems and Applications in Engineering*, vol. 11, no. 1, pp. 241–250, 2023.

[37] Y. Ohno, "Machine learning for lung CT texture analysis: Improvement of inter-observer agreement for radiological finding classification in patients with pulmonary diseases," *European Journal of Radiology*, vol. 134, 2021, doi: 10.1016/j.ejrad.2020.109410.

[38] S. Kiziloluk and E. Sert, "COVID-CCD-Net: COVID-19 and colon cancer diagnosis system with optimized CNN hyperparameters using gradient-based optimizer," *Medical and Biological Engineering and Computing*, vol. 60, no. 6, pp. 1595–1612, 2022, doi: 10.1007/s11517-022-02553-9.

[39] J. M. Ede and R. Beanland, "Adaptive learning rate clipping stabilizes learning," *Machine Learning: Science and Technology*, vol. 1, no. 1, 2020, doi: 10.1088/2632-2153/ab81e2.